



AR9-12-14-18-22-25UFABR

**UNITÀ INTERNA: CANALIZZABILE**

UNITÀ INTERNE		AR9	AR12	AR14	AR18	AR22	AR25
MODELLO							
ALIMENTAZIONE		220-240V-50Hz					
CAPACITA' RAFFREDDAMENTO	KW	2,8	3,50	4,00	5,30	6,00	7,05
	btu/h	9,600	11,900	13,700	18,100	21,100	24,100
CAPACITA' RISCALDAMENTO	KW	3,10	4,10	4,80	5,60	6,30	7,85
	btu/h	10,600	14,000	16,400	19,100	21,500	26,800
POTENZA ASSORBITA	W	32	49		77		155
CORRENTE ASSORBITA		0,20	0,24		0,36		0,68
MASSIMA CORRENTE ASSORBITA		0,24	0,29		0,40		0,84
PORTATA D'ARIA	H gh	420	620		890		1,200
	Med	390	550		840		1,100
	Low	360	470		780		1,000
VELOCITA' VENTOLA	H gh	870	830		1,150		890
	Med	810	750		1,090		820
	Low	760	670		1,020		745
LIVELLO SONORO	H gh	34	33		42		44
	Med	32	29		41		42
	Low	31	27		38		40
DIMENSIONI (HxWxD)	Netto	217x663x595		217x953x595		270x1,210x700	
	Lordo	324x785x686		324x1,075x686		330x1,300x790	
PESO	Netto	18		25		43	
	Lordo	22		29		58	
MISURA TUBI	Liquido	Mm		Ø 6,35			
	Gas	Ø 9,53		Ø 12,7		Ø 15,88	
CONNESSIONE TUBI				A cartella			
RANGE DI TEMPERATURA	Raffredd			18 a 30			
	R scald			16 a 30			

**GENERAL**  
Fujitsu General Limited